Geotechnical Testing Journal
Index to Volume 14
1992

Number	Issue	Pages
1	March	1–88
2	June	89–206
3	September	207–310
4	December	311–423

A

Acar, Y. B. and Nyeretse, P.: Total suction of artificial mixtures of soil compacted at optimum water content, March, 65

Aggregates: Incinerator residue for roads (Aziz and Ramaswamy), Sept., 300

Airey, D. W., Al-Douri, R. H., and Paulos, H. G.: Estimation of pile friction degradation from shearbox tests, Dec., 388

Al-Douri, R. H.
and Poulos, H. C.: Static and cyclic direct shear tests on cabonate sands, June, 138
see Airey, D. W., Al-Douri, R. H., and Paulos, H.

Alfaro, M. C.:
see Bergado, D. T., Daria, P. M., Sampaco, C. L., and Alfaro, M. C.
see Bergado, D. T., Hardiyatimo, H. C., Cisneros, C. B., Chun, J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.

Anderson, L. R.: *see* Bergado, D. T., Hardiyatimo, H. C., Cisneros, C. B., Chun, C. J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.

Anwar, H. A.: *see* Nicholson, P. G., Anwar, H. A., and Seed, R. B.

Arenicz, R. M.: Effect of reinforcement layout on soil strength, June, 158

Atterberg limits: Determination of the plastic limit of a soil by means of a rolling device (Bobrowski and Griekspoor), Sept., 284

Automation: Computer automation of conventional triaxial equipment (Sheahan and Germaine), Dec., 311

Aziz, M. A. and Ramaswamy, S. D.: Incinerator residue for roads, Sept., 300

B

Balasubramaniam, A. S.: *see* Bergado, D. T., Hardiyatimo, H. C., Cisneros, C. B., Chun, C. J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.

Bearing capacity: Determination of deformation properties of collapsible soils (Reznik), Sept., 248

Bentonite: Characteristics of a bentonite slurry as a sealant (Edil and Muhanna), March, 3

Bergado, D. T.,
Daria, P. M., Sampaco, C. L., and Alfaro, M. C.: Authors' closure, June, 198
Hardiyatimo, H. C., Cisneros, C. B., Chun, C. J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.: Pullout resistance of steel geogrids with weathered clay as backfill material, March, 33

Bidimensional materials: "1γ2ε": a new shear apparatus to study the behavior of granular materials (Joer, Lanier, Desrues, and Flavigny), June, 129

Binders: Incinerator residue for roads (Aziz and Ramaswamy), Sept., 300

Blast: Blast-induced liquefaction of an alluvial sand deposit (Charlie, Jacobs, and Doehring), March, 14

Bobrowski, J. J., Jr. and Griekspoor, D. M.: Determination of the plastic limit of a soil by means of a rolling device, Sept., 284

Boháč, J. and Feda, J.: Membrane penetration in triaxial tests, Sept., 288

Brown, P. T.: Bending of a screw plate, March, 80

Budiman, J. S.: *see* Reddy, K. R., Saxena, S. K., and Budiman, J. S.

C

C. A. Hogentogler Award: Introduction to C. A. Hogentogler Award by David I. Stannard (Knodel), March, 47

Calcareous soils: Static and cyclic direct shear tests on carbonate sands (Al-Douri and Poulos), June, 138

Charlie, W. A.
Jacobs, P. J., and Doehring, D. O.: Blast-induced liquefaction of an alluvial sand deposit, March, 14
Johnson, C. F., and Doehring, D. O.: Hollow glass microspheres inhibit blast-induced liquefaction, Dec., 362
see Veyera, G. E., Charlie, W. A., Doehring, D. O., and Hubert, M. E.

Chemical properties: Dispersive behavior of nonswelling clays (Sridharan, Rao, and Dwarkanath), Dec., 380

Cheung, S. C. H.: *see* Mohamed, A. M. O., Yong, R. N., and Cheung, S. C. H.

Choi, J. W. and Ishibashi, I.: Experimental method for determining membrane penetration, Dec., 413

Chu, H.-H. and Vucetic, M.: Settlement of compacted clay in a cyclic direct simple shear device, Dec., 371

Chun, C. B.: *see* Bergado, D. T., Hardiyatimo, H. C., Cisneros, C. B., Chun, C. J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.

Cisneros, C. B.: *see* Bergado, D. T., Hardiyatimo, H. C., Cisneros, C. B., Chun, C. J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.

Clays
Behavior at the shrinkage limit of clay undergoing drying (Williams and Sibley), Sept., 217
Bromhead ring shear test procedure (Stark and Vettel), March, 24
Clay lumps under simulated hydraulic transport conditions (Leshchinsky, Richter, and Fowler), Dec., 393
Dispersive behavior of nonswelling clays (Sridharan, Rao, and Dwarkanath), Dec., 380
Effect of clod size on hydraulic conductivity of compacted clay (Houston and Randeni), June, 123
Leach tests on lime-treated clays (McCallister and Petry), June, 106
New method to measure the effective porosity of clays (Meegoda and Gunasekera), Dec., 340
Properties of some kaolin-based model clay soils (Rossato, Ninis, and Jardine), June, 166
Settlement of compacted clay in a cyclic direct simple shear device (Chu and Vucetic), Dec., 371
Techniques for estimating the longevity of lime-treated expansive clays (McCallister and Petry), Sept., 231

Clay shales: Bromhead ring shear test procedure (Stark and Vettel), March, 24

Clay slurry density: Total stress probe determination of clay slurry density (Tan, Liang, Tan, and Karunaratne), March, 59

Coefficient of consolidation: New method for the determination of coefficient of consolidation (Pandian, Sridharan, and Kumar), March, 74

Cohesionless soils: "1γ2ε": a new shear apparatus to study the behavior of granular materials (Joer, Lanier, Desrues, and Flavigny), June, 129

Collapsing soils: Measurements of matric suction and volume changes during inundation of collapsible soil (Tadepalli, Rahardjo, and Fredlund), June, 115

Compaction: Settlement of compacted clay in a cyclic direct simple shear device (Chu and Vucetic), Dec., 371

Compressibility: Measurement of the pore pressure parameter *C* less than unity in saturated sands (Veyera, Charlie, Doehring, and Hubert), Sept., 223

Computers: Computer automation of conventional triaxial equipment (Sheahan and Germaine), Dec., 311

Consolidation
Authors' closure (Bergado, Daria, Sampaco, and Alfaro), June, 198
Discussion on "prediction of embankment of settlements by in situ tests" by D. T. Bergado, P. M. Daria, C. L. Sampaco, and M. C. Alfaro (Gambin), June, 198

Contaminant transport: New method to measure the effective porosity of clays (Meegoda and Gunasekera), Dec., 340

Cores: Hollow cylinder specimen preparation: cohesive materials (Crockford and Sousa), Sept., 271

Crippa, V.: *see* Lo Presti, D. C. F., Pedroni, S., and Crippa, V.

Crockford, W. W. and Sousa, J.: Hollow cylinder specimen preparation: cohesive materials, Sept., 271

Cyclic loading
Strain-controlled, variable frequency cyclic loading system for soft soils (Kramer, von Laun, and Sivaneswaran), Sept., 264
Strength changes in sand following cyclic shear (Turner and Kulhawy), Sept., 295
Cyclic tests: Estimation of pile friction degradation from shearbox tests (Airey, Al-Douri, and Paulos), Dec., 388
Cylinders: Hollow cylinder specimen preparation: cohesive materials (Crockford and Sousa), Sept., 271

D

Daemen, J. J. K.: *see* Stormont, J. C. and Daemen, J. J. K.
Daria, P. M.: *see* Bergado, D. T., Daria, P. M., Sampaco, C. L., and Alfaro, M. C.
Deformation
Determination of deformation properties of collapsible soils (Reznik), Sept., 248
Measurements of coupled normal deformation, permeability, and heat transfer in rock joints using a triaxial test facility (Zhao), Dec., 323
Deposition intensity: Maximum dry density of cohesionless soils by pluviation and by ASTM D 4253-83: a comparative study (Lo Presti, Pedroni, and Crippa), June, 180
Desrues, J.: *see* Joer, H., Lanier, J., Desrues, J., and Flavigny, E.
Direct shear tests: Static and cyclic direct shear tests on carbonate sands (Al-Douri and Poulos), June, 138
Doehring, D. O.:
see Charlie, W. A., Jacobs, P. J., and Doehring, D. O.
see Charlie, W. A., Johnson, C. F., and Doehring, D. O.
see Veyera, G. E., Charlie, W. A., Doehring, D. O., and Hubert, M. E.
Dredging: Clay lumps under simulated hydraulic transport conditions (Leshchinsky, Richter, and Fowler), Dec., 393
Dwarkanath, H. N.: *see* Sridharan, A., Rao, S. M., and Dwarkanath, H. N.

E

Edil, T. B. and Muhanna, A. S. H.: Characteristics of a bentonite slurry as a sealant, March, 3
Effective stress: Measurement of the pore pressure parameter *C* less than unity in saturated sands (Veyera, Charlie, Doehring, and Hubert), Sept., 223
Elastic modulus: Bending of a screw plate (Brown), March, 80
Electrical properties: New apparatus for the evaluation of electro-kinetic processes in hazardous waste management (Yeung, Sadek, and Mitchell), Sept., 207
Erosion: Dispersive behavior of nonswelling clays (Sridharan, Rao, and Dwarkanath), Dec., 380
Ewen, J. and Thomas, H. R.: Thermal probe—measurement of the thermal conductivity and drying rate of soil in the field, Sept., 256
Explosives
Blast-induced liquefaction of an alluvial sand deposit (Charlie, Jacobs, and Doehring), March, 14
Hollow glass microspheres inhibit blast-induced liquefaction (Charlie, Johnson, and Doehring), Dec., 362

F

Feda, J.: *see* Boháč, J. and Feda, J.
Field tests: Thermal probe—measurement of the thermal conductivity and drying rate of soil in the field (Ewen and Thomas), Sept., 256
Filters: Long-term filtration behavior of soil-geotextile system (Rao, Gupta, and Pradhan), Sept., 238
Finite element analysis: Bending of a screw plate (Brown), March, 80
Flavigny, E.: *see* Joer, H., Lanier, J., Desrues, J., and Flavigny, E.
Flow: Alternate method for determining the Klinkenberg correction (Stormont and Daemen), Dec., 409
Flow clogging: Long-term filtration behavior of soil-geotextile system (Rao, Gupta, and Pradhan), Sept., 238
Fowler, F.: *see* Leshchinsky, D., Richter, S. D., and Fowler, F.
Fracture: Measurements of coupled normal deformation, permeability, and heat transfer in rock joints using a triaxial test facility (Zhao), Dec., 323
Fredlund, D. G.: *see* Tadepalli, R., Rahardjo, H., and Fredlund, D. G.
Frequency: Strain-controlled, variable frequency cyclic loading system for soft soils (Kramer, von Laun, and Sivaneswaran), Sept., 264

G

Gambin, M.: Discussion on "prediction of embankment by settlements by in-situ tests" by D. T. Bergado, P. M. Daria, C. L. Sampaco, and M. C. Alfaro, June, 198
Geogrids: Pullout resistance of steel geogrids with weathered clay as backfill material (Bergado, Hardiyatimo, Cisneros, Chun, Alfaro, Balasubramaniam, and Anderson), March, 33
Geotextiles
Authors' closure (Huang, Holtz, and Wilcox), Sept., 307
Discussion on "effects of back pressure on geotextile transmissivity tests" by An-Ben Huang, Robert D. Holtz, and Ann M. Wilcox (Ling, Tatsuoka, and Wu), Sept., 305
Long-term filtration behavior of soil-geotextile system (Rao, Gupta, and Pradhan), Sept., 238
Thickness equation for nonwoven, needle-punched geotextiles under normal loading (Weggel and Gontar), Dec., 404
Germaine, J. T.: *see* Sheahan, T. C. and Germaine, J. T.
Gontar, W. A.: *see* Weggel, J. R. and Gontar, W. A.
Gradient ratio: Long-term filtration behavior of soil-geotextile system (Rao, Gupta, and Pradhan), Sept., 238
Griekspoor, D. M.: *see* Bobrowski, J. J., Jr. and Griekspoor, D. M.
Ground water: Tensiometers—theory, construction, and use (Stannard), March, 48
Gunasekera, S. D.: *see* Meegoda, N. J. and Gunasekera, S. D.
Gupta, K. K.: *see* Rao, G. V., Gupta, K. K., and Pradhan, M. P. S.

H

Hardiyatimo, H. C.: *see* Bergado, D. T., Hardiyatimo, H. C., Cisneros, C. B., Chun, C. J., Alfaro, M. C., Balasubramaniam, A. S., and Anderson, L. R.
Hazardous waste disposal: New apparatus for the evaluation of electro-kinetic processes in hazardous waste management (Yeung, Sadek, and Mitchell), Sept., 207
Heat of wetting: Behavior at the shrinkage limit of clay undergoing drying (Williams and Sibley), Sept., 217
Holtz, R. D.: *see* Huang, A.-B., Holtz, R. D., and Wilcox, A. M.
Houston, S. L. and Randeni, J. S.: Effect of clod size on hydraulic conductivity of compacted clay, June, 123
Huang, A.-B., Holtz, R. D., and Wilcox, A. M.: Authors' closure, Sept., 307
Hubert, M. E.: *see* Veyera, G. E., Charlie, W. A., Doehring, D. O., and Hubert, M. E.
Hydraulic conductivity
Effect of clod size on hydraulic conductivity of compacted clay (Houston and Randeni), June, 123
New apparatus for the evaluation of electro-kinetic processes in hazardous waste management (Yeung, Sadek, and Mitchell), Sept., 207
Hydraulic fill: Clay lumps under simulated hydraulic transport conditions (Leshchinsky, Richter, and Fowler), Dec., 393

I

Incinerators: Incinerator residue for roads (Aziz and Ramaswamy), Sept., 300
Infiltration: Tensiometers—theory, construction, and use (Stannard), March, 48
In situ tests
Bending of a screw plate (Brown), March, 80
Total stress probe determination of clay slurry density (Tan, Liang, Tan, and Karunaratne), March, 59
Instrumentation
Tensiometers—theory, construction, and use (Stannard), March, 48
Use of air bag system for instrumentation of lateral load tests on previously installed pipe piles (Kramer), Dec., 399
Ishibashi, I.: *see* Choi, J. W. and Ishibashi, I.

J

Jacobs, P. J.: *see* Charlie, W. A., Jacobs, P. J., and Doehring, D. O.
Jardine, R. J.: *see* Rossato, G., Ninis, N. L., and Jardine, R. J.
Joer, H., Lanier, J., Desrues, J., and Flavigny, E.: "1γ2ε": a new shear apparatus to study the behavior of granular materials, June, 129
Johnson, C. F.: *see* Charlie, W. A., Johnson, C. F., and Doehring, D. O.

K

Karunaratne, G.-P.: *see* Tan, S.-A., Liang, K.-M., Tan, T.-S., and Karunaratne, G.-P.

Klinkenberg correction: Alternate method for determining the Klinkenberg correction (Stormont and Daemen), Dec., 409
Knodel, P.: Introduction to C. A. Hogentogler award article by David I. Stannard, March, 47
Koester, J. P.: Influence of test procedure on correlation of Atterberg limits with liquefaction in fine-grained soils, Dec., 352
Kramer, S. L.
Use of air bag system for instrumentation of lateral load tests on previously installed pipe piles, Dec., 399
von Laun, F.-Y., and Sivaneswaran, N.: Strain-controlled, variable frequency cyclic loading system for soft soils, Sept., 264
Kulhawy, F. H.: *see* Turner, J. P. and Kulhawy, F. H.
Kumar, K. S.: *see* Pandian, N. S., Sridharan, A., and Kumar, K. S.

L

Laboratory tests
Development of a true triaxial testing apparatus (Reddy, Saxena, and Budiman), June, 89
Effect of clod size on hydraulic conductivity of compacted clay (Houston and Randeni), June, 123
New apparatus for the evaluation of electrokinetic processes in hazardous waste management (Yeung, Sadek, and Mitchell), Sept., 207
Lanier, J.: *see* Joer, H., Lanier, J., Desrues, J., and Flavigny, E.
Lateral loads: Use of air bag system for instrumentation of lateral load tests on previously installed pipe piles (Kramer), Dec., 399
Leaching
Leach tests on lime-treated clays (McCallister and Petry), June, 106
Techniques for estimating the longevity of lime-treated expansive clays (McCallister and Petry), Sept., 231
Leshchinsky, D., Richter, S. D., and Fowler, F.: Clay lumps under simulated hydraulic transport conditions, Dec., 393
Liang, K.-M.: *see* Tan, S.-A., Liang, K.-M., Tan, T.-S., and Karunaratne, G.-P.
Lime
Leach tests on lime-treated clays (McCallister and Petry), June, 106
Techniques for estimating the longevity of lime-treated expansive clays (McCallister and Petry), Sept., 231
Linearity: New method for the determination of coefficient of consolidation (Pandian, Sridharan, and Kumar), March, 74
Ling, H. I., Tatsuoka, F., and Wu, J. T. H.: Discussion on "effects of back pressure on geotextile transmissivity tests" by An-Ben Huang, Robert D. Holtz, and Ann M. Wilcox, Sept., 305
Liquefaction
Blast-induced liquefaction of an alluvial sand deposit (Charlie, Jacobs, and Doehring), March, 14
Hollow glass microspheres inhibit blast-induced liquefaction (Charlie, Johnson, and Doehring), Dec., 362
Influence of test procedure on correlation of Atterberg limits with liquefaction in fine-grained soils (Koester), Dec., 352
Liquid limit
Determination of the plastic limit of a soil by means of a rolling device (Bobrowski and Griekspoor), Sept., 284
Influence of test procedure on correlation of Atterberg limits with liquefaction in fine-grained soils (Koester), Dec., 352
Loading
Static and cyclic direct shear tests on carbonate sands (Al-Douri and Poulos), June, 138
Strain-controlled, variable frequency cyclic loading system for soft soils (Kramer, von Laun, and Sivaneswaran), Sept., 264
Thickness equation for nonwoven, needle-punched geotextiles under normal loading (Weggel and Gontar), Dec., 404
Loess: Determination of deformation properties of collapsible soils (Reznik), Sept., 248
Longevity: Techniques for estimating the longevity of lime-treated expansive clays (McCallister and Petry), Sept., 231
Look, B. G. and Reeves, I. N.: Application of time domain reflectometry in geotechnical instrumentation, Sept., 277
Lo Presti, D. C. F., Pedroni, S., and Crippa, V.: Maximum dry density of cohesionless soils by pluviation and by ASTM D 4253–83: a comparative study, June, 180

M

Matrix: Measurements of matric suction and volume changes during inundation of collapsible soil (Tadepalli, Rahardjo, and Fredlund), June, 115
Maximum dry density: Maximum dry density of cohesionless soils by pluviation and by ASTM D 4253–83: a comparative study (Lo Presti, Pedroni, and Crippa), June, 180
McCallister, L. D.
and Petry, T. M.: Leach tests on lime-treated clays, June, 106
and Petry, T. M.: Techniques for estimating the longevity of lime-treated expansive clays, Sept., 231
Meegoda, N. J. and Gunasekera, S. D.: New method to measure the effective porosity of clays, Dec., 340
Membrane compliance: Injection-correction system to mitigate membrane compliance (Nicholson, Anwar, and Seed), June, 190
Membranes
Experimental method for determining membrane penetration (Choi and Ishibashi), Dec., 413
Injection-correction system to mitigate membrane compliance (Nicholson, Anwar, and Seed), June, 190
Membrane penetration in triaxial tests (Boháč and Feda), Sept., 288
Mitchell, J. K.: *see* Yeung, A. T., Sadek, S. M., and Mitchell, J. K.
Model soils: Properties of some kaolin-based model clay soils (Rossato, Ninis, and Jardine), June, 166
Mohamed, A. M. O., Yong, R. N. and Cheung, S. C. H.: Temperature dependence of soil water potential, Dec., 330
Moisture content: Tensiometers—theory, construction, and use (Stannard), March, 48
Muhanna, A. S. H.: *see* Edil, T. B. and Muhanna, A. S. H.

N

Nicholson, P. G., Anwar, H. A., and Seed, R. B.: Injection-correction system to mitigate membrane compliance, June, 190
Ninis, N. L.: *see* Rossato, G., Ninis, N. L., and Jardine, R. J.
Nyeretse, P.: *see* Acar, Y. B. and Nyeretse, P.

P

Pandian, N. S., Sridharan, A., and Kumar, K. S.: New method for the determination of coefficient of consolidation, March, 74
Paulos, H. G.: *see* Airey, D. W., Al-Douri, R. H., and Paulos, H. G.
Pedroni, S.: *see* Lo Presti, D. C. F., Pedroni, S., and Crippa, V.
Permeability
Alternate method for determining the Klinkenberg correction (Stormont and Daemen), Dec., 409
Authors' closure (Huang, Holtz, and Wilcox), Sept., 307
Discussion on "effects of back pressure on geotextile transmissivity tests" by An-Ben Huang, Robert D. Holtz, and Ann M. Wilcox (Ling, Tatsuoka, and Wu), Sept., 305
Effect of clod size on hydraulic conductivity of compacted clay (Houston and Randeni), June, 123
Leach tests on lime-treated clays (McCallister and Petry), June, 106
Petry, T. M.: *see* McCallister, L. D. and Petry, T. M.
Piles
Estimation of pile friction degradation from shearbox tests (Airey, Al-Douri, and Paulos), Dec., 388
Use of air bag system for instrumentation of lateral load tests on previously installed pipe piles (Kramer), Dec., 399
Plasticity: Total suction of artificial mixtures of soil compacted at optimum water content (Acar and Nyeretse), March, 65
Plasticity index
Clay lumps under simulated hydraulic transport conditions (Leshchinsky, Richter, and Fowler), Dec., 393
Determination of the plastic limit of a soil by means of a rolling device (Bobrowski and Griekspoor), Sept., 284
Plastic limit
Determination of the plastic limit of a soil by means of a rolling device (Bobrowski and Griekspoor), Sept., 284
Influence of test procedure on correlation of Atterberg limits with liquefaction in fine-grained soils (Koester), Dec., 352
Plastics: Experimental method for determining membrane penetration (Choi and Ishibashi), Dec., 413
Pluviation: Maximum dry density of cohesionless soils by pluviation and by ASTM D 4253–83: a comparative study (Lo Presti, Pedroni, and Crippa), June, 180
Pore pressure parameter *C*: Measurement of the pore pressure parameter *C* less than unity in saturated sands (Veyera, Charlie, Doehring, and Hubert), Sept., 223
Porosity: New method to measure the effective porosity of clays (Meegoda and Gunasekera), Dec., 340
Poulos, H. C.: *see* Al-Douri, R. H. and Poulos, H. C.

Pradhan, M. P. S.: *see* Rao, G. V., Gupta, K. K., and Pradhan, M. P. S.
Pressures
Authors' closure (Bergado, Daria, Sampaco, and Alfaro), June, 198
Discussion on "prediction of embankment of settlements by in-situ tests" by D. T. Bergado, P. M. Daria, C. L. Sampaco, and M. C. Alfaro (Gambin), June, 198

R

Rahardjo, H.: *see* Tadepalli, R., Rahardjo, H., and Fredlund, D. G.
Ramaswamy, S. D.: *see* Aziz, M. A. and Ramaswamy, S. D.
Randeni, J. S.: *see* Houston, S. L. and Randeni, J. S.
Rao, G. V., Gupta, K. K., and Pradhan, M. P. S.: Long-term filtration behavior of soil-geotextile system, Sept., 238
Rao, S. M.: *see* Sridharan, A., Rao, S. M., and Dwarkanath, H. N.
Reclamation: Total stress probe determination of clay slurry density (Tan, Liang, Tan, and Karunaratne), March, 59
Reddy, K. R., Saxena, S. K., and Budiman, J. S.: Development of a true triaxial testing apparatus, June, 89
Reeves, I. N.: *see* Look, B. G. and Reeves, I. N.
Refuse disposal: Incinerator residue for roads (Aziz and Ramaswamy), Sept., 300
Reinforcement
Effect of reinforcement layout on soil strength (Arenicz), June, 158
Pullout resistance of steel geogrids with weathered clay as backfill material (Bergado, Hardiyatimo, Cisneros, Chun, Alfaro, Balasubramaniam, and Anderson), March, 33
Residual strength: Bromhead ring shear test procedure (Stark and Vettel), March, 24
Reznik, Y. M.: Determination of deformation properties of collapsible soils, Sept., 248
Richter, S. D.: *see* Leshchinsky, D., Richter, S. D., and Fowler, F.
Rock joint: Measurements of coupled normal deformation, permeability, and heat transfer in rock joints using a triaxial test facility (Zhao), Dec., 323
Rossato, G., Ninis, N. L., and Jardine, R. J.: Properties of some kaolin-based model clay soils, June, 166

S

Sadek, S. M.: *see* Yeung, A. T., Sadek, S. M., and Mitchell, J. K.
Sampaco, C. L.: *see* Bergado, D. T., Daria, P. M., Sampaco, C. L., and Alfaro, M. C.
Sand
Blast-induced liquefaction of an alluvial sand deposit (Charlie, Jacobs, and Doehring), March, 14
Development of a true triaxial testing apparatus (Reddy, Saxena, and Budiman), June, 89
Estimation of pile friction degradation from shearbox tests (Airey, Al-Douri, and Paulos), Dec., 388
Measurement of the pore pressure parameter *C* less than unity in saturated sands (Veyera, Charlie, Doehring, and Hubert), Sept., 223
Membrane penetration in triaxial tests (Boháč and Feda), Sept., 288
Strength changes in sand following cyclic shear (Turner and Kulhawy), Sept., 295
Saturation: Hollow glass microspheres inhibit blast-induced liquefaction (Charlie, Johnson, and Doehring), Dec., 362
Saxena, S. K.: *see* Reddy, K. R., Saxena, S. K., and Budiman, J. S.
Screw plates: Bending of a screw plate (Brown), March, 80
Screw plate test
Authors' closure (Bergado, Daria, Sampaco, and Alfaro), June, 198
Discussion on "prediction of embankment of settlements by in-situ tests" by D. T. Bergado, P. M. Daria, C. L. Sampaco, and M. C. Alfaro), June, 198
Sealants: Characteristics of a bentonite slurry as a sealant (Edil and Muhanna), March, 3
Seed, R. B.: *see* Nicholson, P. G., Anwar, H. A., and Seed, R. B.
Settlement
Authors' closure (Bergado, Daria, Sampaco, and Alfaro), June, 198
Discussion on "prediction of embankment of settlements by in-situ tests" by D. T. Bergado, P. M. Daria, C. L. Sampaco, and M. C. Alfaro), June, 198
Sheahan, T. C. and Germaine, J. T.: Computer automation of conventional triaxial equipment, Dec., 311
Shear strength: Strength changes in sand following cyclic shear (Turner and Kulhawy), Sept., 295
Shear tests: Settlement of compacted clay in a cyclic direct simple shear device (Chu and Vucetic), Dec., 371
Shrinkage desiccation: Behavior at the shrinkage limit of clay undergoing drying (Williams and Sibley), Sept., 217
Shrinkage limit: Behavior at the shrinkage limit of clay undergoing drying (Williams and Sibley), Sept., 217
Sibley, J. W.: *see* Williams, D. J. and Sibley, J. W.
Sivaneswaran, N.: *see* Kramer, S. L., von Laun, F.-Y., and Sivaneswaran, N.
Skin friction: Estimation of pile friction degradation from shearbox tests (Airey, Al-Douri, and Paulos), Dec., 388
Slurries: Characteristics of a bentonite slurry as a sealant (Edil and Muhanna), March, 3
Soil dielectric: Application of time domain reflectometry in geotechnical instrumentation (Look and Reeves), Sept., 277
Soil reinforcement
Effect of reinforcement layout on soil strength (Arenicz), June, 158
Pullout resistance of steel geogrids with weathered clay as backfill material (Bergado, Hardiyatimo, Cisneros, Chun, Alfaro, Balasubramaniam, and Anderson), March, 33
Soil water potential: Temperature dependence of soil water potential (Mohamed, Yong, and Cheung), Dec., 330
Soils
Determination of deformation properties of collapsible soils (Reznik), Sept., 248
Effect of reinforcement layout on soil strength (Arenicz), June, 158
Influence of test procedure on correlation of Atterberg limits with liquefaction in fine-grained soils (Koester), Dec., 352
New method to measure the effective porosity of clays (Meegoda and Gunasekera), Dec., 340
Pullout resistance of steel geogrids with weathered clay as backfill material (Bergado, Hardiyatimo, Cisneros, Chun, Alfaro, Balasubramaniam, and Anderson), March, 33
Strain-controlled, variable frequency cyclic loading system for soft soils (Kramer, von Laun, and Sivaneswaran), Sept., 264
Temperature dependence of soil water potential (Mohamed, Yong, and Cheung), Dec., 330
Thermal probe—measurement of the thermal conductivity and drying rate of soil in the field (Ewen and Thomas), Sept., 256
Total suction of artificial mixtures of soil compacted at optimum water content (Acar and Nyeretse), March, 65
Sousa, J.: *see* Crockford, W. W. and Sousa, J.
Sridharan, A.
Rao, S. M., and Dwarkanath, H. N.: Dispersive behavior of nonswelling clays, Dec., 380
see Pandian, N. S., Sridharan, A., and Kumar, K. S.
Stannard, D. I.: Tensiometers—theory, construction, and use, March, 48
Stark, T. D. and Vettel, J. J.: Bromhead ring shear test procedure, March, 24
Stormont, J. C. and Daemen, J. J. K.: Alternate method for determining the Klinkenberg correction, Dec., 409
Strain: "1γ2ε": a new shear apparatus to study the behavior of granular materials (Joer, Lanier, Desrues, and Flavigny), June, 129
Stress
Development of a true triaxial testing apparatus (Reddy, Saxena, and Budiman), June, 89
"1γ2ε": a new shear apparatus to study the behavior of granular materials (Joer, Lanier, Desrues, and Flavigny), June, 129
Suction
Measurements of matric suction and volume changes during inundation of collapsible soil (Tadepalli, Rahardjo, and Fredlund), June, 115
Total suction of artificial mixtures of soil compacted at optimum water content (Acar and Nyeretse), March, 65
Swelling
Temperature dependence of soil water potential (Mohamed, Yong, and Cheung), Dec., 330
Total suction of artificial mixtures of soil compacted at optimum water content (Acar and Nyeretse), March, 65

T

Tadepalli, R., Rahardjo, H., and Fredlund, D. G.: Measurements of matric suction and volume changes during inundation of collapsible soil, June, 115
Tan, S.-A., Liang, K.-M., Tan, T.-S., and Karunaratne, G.-P.: Total stress probe determination of clay slurry density, March, 59
Tan, T.-S.: *see* Tan, S.-A., Liang, K.-M., Tan, T.-S., and Karunaratne, G.-P.

Tatsuoka, F.: *see* Ling, H. I., Tatsuoka, F., and Wu, J. T. H.
Temperature: Temperature dependence of soil water potential (Mohamed, Yong, and Cheung), Dec., 330
Thermal conductivity: Thermal probe—measurement of the thermal conductivity and drying rate of soil in the field (Ewen and Thomas), Sept., 256
Thickness: Thickness equation for nonwoven, needle-punched geotextiles under normal loading (Weggel and Gontar), Dec., 404
Thomas, H. R.: *see* Ewen, J. and Thomas, H. R.
Time domain reflectivity: Application of time domain reflectometry in geotechnical instrumentation (Look and Reeves), Sept., 277
Total stress probe: Total stress probe determination of clay slurry density (Tan, Liang, Tan, and Karunaratne), March, 59
Transmissivity
Authors' closure (Huang, Holtz, and Wilcox), Sept., 307
Discussion on "effects of back pressure on geotextile transmissivity tests" by An-Ben Huang, Robert D. Holtz, and Ann M. Wilcox (Ling, Tatsuoka, and Wu), Sept., 305
Triaxial tests
Alternate method for determining the Klinkenberg correction (Stormont and Daemen), Dec., 409
Computer automation of conventional triaxial equipment (Sheahan and Germaine), Dec., 311
Development of a true triaxial testing apparatus (Reddy, Saxena, and Budiman), June, 89
Experimental method for determining membrane penetration (Choi and Ishibashi), Dec., 413
Hollow cylinder specimen preparation: cohesive materials (Crockford and Sousa), Sept., 271
Injection-correction system to mitigate membrane compliance (Nicholson, Anwar, and Seed), June, 190
Measurements of coupled normal deformation, permeability, and heat transfer in rock joints using a triaxial test facility (Zhao), Dec., 323
Membrane penetration in triaxial tests (Boháč and Feda), Sept., 288
Properties of some kaolin-based model clay soils (Rossato, Ninis, and Jardine), June, 166
Strain-controlled, variable frequency cyclic loading system for soft soils (Kramer, von Laun, and Sivaneswaran), Sept., 264
Turner, J. P. and Kulhawy, F. H.: Strength changes in sand following cyclic shear, Sept., 295

V

Vettel, J. J.: *see* Stark, T. D. and Vettel, J. J.
Veyera, G. E., Charlie, W. A., Doehring, D. O., and Hubert, M. E.: Measurement of the pore pressure parameter *C* less than unity in saturated sands, Sept., 223
Viscosity: Characteristics of a bentonite slurry as a sealant (Edil and Muhanna), March, 3
Volume: Measurements of matric suction and volume changes during inundation of collapsible soil (Tadepalli, Rahardjo, and Fredlund), June, 115
Volumetric moisture content: Application of time domain reflectometry in geotechnical instrumentation (Look and Reeves), Sept., 277
von Laun, F.-Y.: *see* Kramer, S. L., von Laun, F.-Y., and Sivaneswaran, N.
Vucetic, M.: *see* Chu, H.-H. and Vucetic, M.

W–Z

Weggel, J. R. and Gontar, W. A.: Thickness equation for nonwoven, needle-punched geotextiles under normal loading, Dec., 404
Wilcox, A. M.: *see* Huang, A.-B., Holtz, R. D., and Wilcox, A. M.
Williams, D. J. and Sibley, J. W.: Behavior at the shrinkage limit of clay undergoing drying, Sept., 217
Wu, J. T. H.: *see* Ling, H. I., Tatsuoka, F., and Wu, J. T. H.
Yeung, A. T., Sadek, S. M., and Mitchell, J. K.: New apparatus for the evaluation of electro-kinetic processes in hazardous waste management, Sept., 207
Yong, R. N.: *see* Mohamed, A. M. O., Yong, R. N. and Cheung, S. C. H.
Zhao, J.: Measurements of coupled normal deformation, permeability, and heat transfer in rock joints using a triaxial test facility, Dec., 323